

(19) World Intellectual Property  
Organization  
International Bureau



556357

(43) International Publication Date  
25 November 2004 (25.11.2004)

PCT

(10) International Publication Number  
WO 2004/102005 A1

(51) International Patent Classification<sup>7</sup>: F04C 29/02, 23/00

(21) International Application Number:  
PCT/JP2004/007133

(22) International Filing Date: 19 May 2004 (19.05.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
2003-139770 19 May 2003 (19.05.2003) JP  
2003-139771 19 May 2003 (19.05.2003) JP  
2003-139772 19 May 2003 (19.05.2003) JP

(71) Applicant (for all designated States except US): MATSUSHITA ELECTRIC INDUSTRIAL CO., LTD. [JP/JP]; 1006, Oaza Kadoma, Kadoma-shi, Osaka 571-8501 (JP).

(72) Inventors; and

(75) Inventors/Applicants (for US only): HASEGAWA, Hiroshi. OKAICHI, Atsuo. NISHIWAKI, Fumitoshi.

(74) Agents: SHIMIZU, Yoshihiro et al.; 3rd Floor, Yashiro Building, 14-4, Takadanobaba 2-chome, Shinjuku-ku, Tokyo 169-0075 (JP).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: COMPRESSOR



(57) Abstract: A compressor comprising a hermetical container, a compression mechanism disposed in a lower portion in the hermetical container, a rotational motor disposed in an upper portion in the hermetical container and having a stator and a rotor, coil ends provided on upper end lower ends of the stator, a discharge pipe provided on an upper end of the hermetical container, and an oil reservoir provided in a lower portion in the hermetical container, in which working fluid compressed by the compression mechanism is introduced into an upper space of the hermetical container from a gap between the rotational motor and the hermetical container, and the working fluid is discharged out from the hermetical container through the discharge pipe, wherein an open end in the hermetical container of the discharge pipe is located inside the upper end coil end.

WO 2004/102005 A1